



LED 3W	Ra 90	2 SDCM	200 lumen	900 mA	-20 °C ... +50 °C	
DIM	IP44	16 / 30 / 60° OVAL	 22 mm	2200K 2700K 3000K 4000K	L90B10 50 000h	CE

		Sähkönumerot	E-Nummer	Product numbers
saas blaze white 16		2200K 41 314 57	74 767 26	1000 2636
		2700K 41 314 59	74 767 27	1000 2637
		3000K 41 314 60	74 767 28	1000 2638
		4000K 41 314 61	74 767 29	1000 2639
saas blaze grey amber 16		2200K 41 314 74	74 767 42	1000 2654
		2700K 41 314 75	74 767 43	1000 2655
		3000K 41 314 76	74 767 44	1000 2656
		4000K 41 314 77	74 767 45	1000 2657
saas blaze black 16		2200K 41 314 66	74 767 34	1000 2646
		2700K 41 314 67	74 767 35	1000 2647
		3000K 41 314 68	74 767 36	1000 2648
		4000K 41 314 69	74 767 37	1000 2649
saas blaze white 30		2200K 41 314 62	74 767 30	1000 2640
		2700K 41 314 63	74 767 31	1000 2642
		3000K 41 314 64	74 767 32	1000 2644
		4000K 41 314 65	74 767 33	1000 2645
saas blaze grey amber 30		2200K 41 314 78	74 767 46	1000 2658
		2700K 41 314 79	74 767 47	1000 2659
		3000K 41 314 80	74 767 48	1000 2660
		4000K 41 314 81	74 767 49	1000 2661
saas blaze black 30		2200K 41 314 70	74 767 38	1000 2650
		2700K 41 314 71	74 767 39	1000 2651
		3000K 41 314 72	74 767 40	1000 2652
		4000K 41 314 73	74 767 41	1000 2653